HD4V

VACUUM/PRESSURE PUMP

(CCW OR CW)

165 CFM



Over 115 Years of Excellence

Masport Rotary Vane Pumps are designed and engineered to give you the reliable pumping performance you need for the task at hand. With long hours and waste to be removed, you need a pump you can rely on. With over 100 years of experience in the vacuum/pressure pump industry, you can be confident in choosing Masport pumps and systems for your vacuum pump needs.

Built to work as hard as you do.

CUSTOMER SERVICE WHEN YOU NEED IT

Our customers are our top priority. Any questions you have about your vacuum pump set-up, we're help you along the way.



QUALITY & PERFORMANCE

- Designed for Tank Sizes up to 1,500 gallons
- 165 CFM
- 1 1/2" NPT Connections
- Air Cooled
- Available in CW/CCW Rotations
- Achieve Minimum 27"HG (Intermittent)
- ▶ 1-Year Performance Warranty

DESIGNED FOR DURABILITY & EASY OPERATION

- Heat Stabilized Kevlar Vanes
- Heavy-Duty Bearings and Viton Oil Seals
 - For longer pump life
- **▶** Durable, High-Temperature, Translucent Oil Lines
- **▶** End Thrust Protection
 - Prevents rotor-to-end cover contact and wear

INTEGRATED COMPONENTS

- · Pump Identifier Tag with QR Code
 - o Quickly scan for replacement parts, manuals, and more
- Oil Pump Cover
 - o To protect the life of oil pump
- Automatic Beka Oil Pump



HD4V // VACUUM / PRESSURE PUMP

Performance Data - Vacuum

PUMP	DISPLACEMENT C.F.M	S.C.F.M and A.C.F.M @ VACUUM								MAXIMUM VACUUM – "Hq				
R.P.M			5	10	15	18	20	22	24	25	26	27	CONTINUOUS	INTERMITTENT
4400	122	SCFM	103	78	57	41	33	23	15	12	7.2	3.7	20	27
1100		ACFM	121	117	114	103	99	86	75	72	53	37	20	
4225	137	SCFM	116	88	63	46	37	26	16	14	9.6	4.1	20	27
1225		ACFM	136	132	127	115	111	97	80	78	71	41		
1400	165	SCFM	132	100	72	53	42	30	19	16	11	4.7	20	27
		ACFM	155	150	145	132	126	112	95	84	81	47		27

Performance Data - Pressure


PUMP	DISPLACEMENT C.F.M			MAXIMUM PRESSURE – P.S.I.G						
R.P.M		5	10	15	18	20	25	30	CONTINUOUS INTERMIT	INTERMITTENT
1100	122	102	97	93	87	82	77	72	20	30
1225	137	115	109	104	98	92	87	81	20	30
1400	165	131	125	119	112	105	99	92	20	30

Horsepower Required @ "Hg

PUMP	VACUUM "Hg								
R.P.M	5	10	15	20	27				
1100	4.4	4.7	4.9	5.4	5.9				
1225	4.9	5.2	5.5	6.0	6.6				
1400	5.6	5.9	6.3	6.9	7.5				

Horsepower Required @ P.S.I.G

PUMP	P.S.I.G								
R.P.M	5	10	15	20	27				
1100	4.9	6.9	8.7	10.7	12.4				
1225	5.5	7.7	9.7	11.9	13.8				
1400	6.3	8.8	11.0	13.6	15.8				



Explore more pumping supplies online at MASPORTPUMP.COM



Pump Replacement Parts Rebuild, Gasket & Seal, and Vane Kits



Pump Fluids
Vacuum Pump Oil and
Flushing Fluid



Vacuum Tank ComponentsSight Glasses, Oil Separators,
Scrubbers, and more.



Gearboxes, Couplers, and BasesSuperior Brand Gearboxes, Rexnord & Woods Couplers, and more.